

**KVM Console Drawer Switch  
ADE-5701 (LCD KVM)**



Push & Press  
EZ-5701/5708/5716(Drawer KVM)  
8/16-computer ports  
Switch Operation: hot key for Win NT/9x/Me/2000/XP;  
Linux/Unix; Novell

**Product Features**

3 in 1 console drawer - a 17" TFT-LCD, keyboard & touch pad integrated in a 1U high & 19" rack mountable unit (without KVM Switch)

4 in 1 console drawer - a console drawer with built-in 8/16 port KVM Switch

3 layers daisy-chain allow to control up to 2048/4096 computers from console drawer

No software or interface card required, plug-n-play

Convenient computer selection via user-friendly **On Screen Display (OSD)** menu or **Hot Key** combinations or select button on the LCD Panel

AutoScan feature for monitoring selected or power on computers

Hot pluggable - add or remove computers without power down the switch

Auto-sensing of computer port on daisy chained installations

Two level password protection - 4 authorized users & an administrator view & control the authorized computers - separate setting for each authorized users

Special port protection - a port lock for administrator single port lock function

PS/2 keyboard & mouse emulation - computers boot even when the console focus is elsewhere

15" RGB analog TFT-LCD display support high XGA resolutions of up to 1024 x 768 with 250cd/m (sq) brightness & 350:1 contrast

### Technical Specifications

Model	EZ-5708	EZ-5716
Computer Connection Number		
Daisy Chain	2048	4096
Direct	8	16
Computer Connector		
Keyboard, Mouse	PS/2	HDB-15 Female
Monitor	HDB-15 male	
Console Connector Type		
Keyboard, Mouse	PS/2	PS/2
Monitor	HDB-15 Female	HDB-15 Female
Cable Type	PS/2 KVM Cable	Special 3-in-1 Cable
Applicable to Computer	PS/2 PC, Sun+, Mac	PS/2 PC, Sun+, Mac
Port Selection	Hot Key ; Button ; OSD	Hot Key ; Button ; OSD
LEDs	8 (Red) 8 (Blue)	16 (Red) 16 (Blue)
Power Consumption	120V, 60Hz, 24W ; 230V, 50Hz, 24W	120V, 60Hz, 24W ; 230V, 50Hz, 24W
Video Resolution	1280 x 1024 ; 17" TFT LCD	1280 x 1024; 17" TFT LCD
Rack-Mounted	19" Industry-standard	19" Industry-standard
Automatic Scan Interval	3-255 / seconds	3-255 / seconds
Rear-mount Brackets	1U-height, Included	1U-height, Included
Housing	Metal	Metal
Humidity	0-80%RH	0-80%RH
Dimensions (mm)	L114* W404* H40mm	L114* W404* H40mm

### User

Enterprise  
 Server Room (MIS)  
 Research Institute  
 ISP/IDC  
 Testing