



FOCUS-103 IP CAMERA

Introduction :

SIXCOM IP-Cam is a colorful camera with a built-in IP address, Ethernet Software Stacks and Protocols. Plugging SIXCOM IP-Cam directly to a RJ45 Ethernet port and watch the camera site from anywhere around the world. Connecting directly to Ethernet networks, SIXCOM IP-Cam is a stand-alone digital network camera requiring no extra server at the camera site. With the motion detection trigger function, SIXCOM IP-Cam will provide you with the necessary security with the easiest installation

Features :

- Built-in Micphone with Audio / Video Function
- Real-Time Motion Detection
- Support TCP/IP, SMTP, FTP, PPPoE, DHCP (Dynamic Host Configuration Protocol)
- Built-in web server allows camera to be accessed by standard Internet browser
- Network RJ45: 10Base-T/100Base-TX Ethernet networks
- Network ready, IP addressable (no PC is required)
- Motion-JPEG based compression
- 4different resolutions: 640x480, 352x288, 160x120, 320x240
- Record AVI or Motion JPEG images on to hard disk for future viewing
- Simultaneous Viewers: 25
- Multi video display (Max 9 video)

Specification :

- Built-in Micphone with Audio / Video Function
- Stand-alone network camera for flexible installation
- Simple installation and multiple mounting methods
- Embedded Web Server Supported
- No computer needed at the monitored site
- Access live video web browser any time, any place for remote surveillance and management
- 2default HTTP Ports supported. They can be changed to fit different network environment
- Built-in Motion Detection for security with no extra cost
- Standard JPEG Image Format
- Record AVI or Motion JPEG images into hard disk for future viewing
- Capture photos and video to your PC

- Password protection, Supervisor password system for you to decide who is authorized to browse the camera, for E-mail and FTP alert
- E-Mail the Detected images to preset FTP Server
- Direct connecting to ADSL by PPPoE, mail the IP setting to pre-set mail address
- 4selectable image resolutions and 2 image quality settings
- 2selectable frequency: 50Hz and 60Hz
- Unlimited number of users concurrently browsing the same camera
- E-Mail notification for sharing or notifying information actively to the connected party
- Camera ID name configurable
- Web-based configuration interface
- LAN/WAN interface supported
- Support Fixed IP or Dynamic IP by DHCP (Dynamic Host Configuration Protocol)
- Log List report
- Audio Format: PCM, ADPCM
- DDNS Server support
- IP forwarding Server support
- Remote reboot
- On line Firmware update
- Multi video display (Max 9 video)
- Hardware reset button

Accessories Include :

IP-Cam, RJ-45 Cable, Power Adapter, CD-ROM, Manual

