



GPL015



ITEM	GPL150 DC 12V	GPL150 DC 24V
OUTPUT POWER	150W CONTINUOUS POWER 450W SURGE POWER	150W CONTINUOUS POWER 450W SURGE POWER
STANDBY CURRENT	DC 12V < 0.21A	DC 24V < 0.13A
INPUT VOLTAGE	DC 10V ~ 15V	DC 20V ~ 30V
OUTPUT VOLTAGE	AC 100V, 110V, 220V, 230V, 240V	AC 100V, 110V, 220V, 230V, 240V
OUTPUT WAVE FORM	Modified Sine Wave 	Modified Sine Wave 
EFFICIENCY	90%	90%
<input type="checkbox"/> INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. Ex. 12V / 24V	AUTO-DETECTING WRONG BATTERY CONT. Ex. 12V / 24V
<input type="checkbox"/> OUTPUT REGULATION	± 5% INTELLIGENT AVR	± 5% INTELLIGENT AVR
<input type="checkbox"/> OUTPUT FREQUENCY	50Hz / 60Hz ± 0.05% CRYSTAL CONTROLLED.	50Hz / 60Hz ± 0.05% CRYSTAL CONTROLLED.
PROTECTIONS:		
<input type="checkbox"/> OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION	OUTPUT SHORT CIRCUIT PROTECTION
<input type="checkbox"/> LOW BATTERY	< 11V ± 0.5V PRE-ALARM < 10 V ± 0.5V SHUT DOWN & ALARM	< 22V ± 0.5V PRE-ALARM < 20.5V ± 0.5V SHUT DOWN & ALARM
<input type="checkbox"/> OVER HEATING	> 60° PRE-ALARM > 65° SHUT DOWN & ALARM	> 60° PRE-ALARM > 65° SHUT DOWN & ALARM
<input type="checkbox"/> OVER LOAD	> 150W PRE-ALARM > 200W SHUT DOWN & ALARM	> 150W PRE-ALARM > 200W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE	BY FUSE
FUSE	DC 12V : 15A * 1PC	DC 24V : 10A * 1PC
AC OUTLET	1 AC OUTLET	1 AC OUTLET
DIMENSIONS (L*W*H)	120 * 45 * 73 mm (US//JAPAN) 120 * 73 * 73 mm (EUROPE)	120 * 45 * 73 mm (US//JAPAN) 120 * 73 * 73 mm (EUROPE)
NET WEIGHT	0.46KG (US/JAPAN) 0.56KGS (EUROPE)	0.46KG (US/JAPAN) 0.56KGS (EUROPE)
<input type="checkbox"/> MARK ARE OUR UNIQUE FUNCTIONS		

Mark Are Our Unique Functions